

# Custom Items

The custom item event is a startup event.

Custom items are created in a startup script. They cannot be reloaded without restarting the game. The event is not cancellable.

```
// Listen to item registry event
StartupEvents.registry('item', e => {
  // The texture for this item has to be placed in kubejs/assets/kubejs/textures/item/test_item.png
  // If you want a custom item model, you can create one in Blockbench and put it in
  kubejs/assets/kubejs/models/item/test_item.json
  e.create('test_item')

  // If you want to specify a different texture location you can do that too, like this:
  e.create('test_item_1').texture('mobbo:item/lava') // This texture would be located at
  kubejs/assets/mobbo/textures/item/lava.png

  // You can chain builder methods as much as you like
  e.create('test_item_2').maxStackSize(16).glow(true)

  // You can specify item type as 2nd argument in create(), some types have different available methods
  e.create('custom_sword', 'sword').tier('diamond').attackDamageBaseline(10.0)
})
```

Valid item types:



- basic (this is the default)
- sword
- pickaxe
- axe
- shovel
- shears
- hoe
- helmet
- chestplate

- leggings
- boots

Other methods item builder supports: [you can chain these methods after create()]

- `maxStackSize(size)`
- `displayName(name)`
- `unstackable()`
- `maxDamage(damage)` This is the item's durability, not actual weapon damage.
- `burnTime(ticks)`
- `containerItem(item_id)`
- `rarity('rarity')`
- `tool(type, level)`
- `glow(true/false)`
- `tooltip(text...)`
- `group('group_id')`
- `color(index, colorHex)`
- `texture(customTextureLocation)`
- `parentModel(customParentModelLocation)`
- `food(foodBuilder => ...)` For full syntax see below

Methods available if you use a tool type ( `'sword'`, `'pickaxe'`, `'axe'`, `'shovel'` or `'hoe'` ):

- `tier('toolTier')`
- `modifyTier(tier => ...)` Same syntax as custom tool tier, see [Custom Tiers](#)
- `attackDamageBaseline(damage)` You only want to modify this if you are creating a custom weapon such as Spear, Battleaxe, etc.
- `attackDamageBonus(damage)`
- `speedBaseline(speed)` Same as `attackDamageBaseline`, only modify for custom weapon types
- `speed(speed)`

Default available tool tiers:

- wood
- stone
- iron
- gold
- diamond
- netherite

Methods available if you use an armour type ( `'helmet'`, `'chestplate'`, `'leggings'` or `'boots'` ):



- `tier('armorTier')`
- `modifyTier(tier => ...)` Same syntax as custom armor tier, see [Custom Tiers](#)

Default available armor tiers:



- leather
- chainmail
- iron
- gold
- diamond
- turtle
- netherite

Vanilla group/creative tab IDs:



- search
- buildingBlocks
- decorations
- redstone
- transportation
- misc
- food
- tools
- combat
- brewing

## Custom Foods

```
StartupEvents.registry('item', event => {
  event.create('magic_steak').food(food => {
    food
    hunger(6)
    saturation(6)//This value does not directly translate to saturation points gained
    //The real value can be assumed to be:
    //min(hunger * saturation * 2 + saturation, foodAmountAfterEating)
    effect('speed', 600, 0, 1)
    removeEffect('poison')
    alwaysEdible()//Like golden apples
    fastToEat()//Like dried kelp
  })
})
```

```

    ctx.meat()//Dogs are willing to eat it
    ctx.eaten(ctx => { //runs code upon consumption
        ctx.player.tell(Text.gold('Yummy Yummy!'))
        //If you want to modify this code then you need to restart the game.
        //However, if you make this code call a global startup function
        //and place the function *outside* of an event handler
        //then you may use the command:
        // /kubejs reload startup_scripts
        //to reload the function instantly.
        //See example below
    })
  })

event.create('magicer_steam').unstackable().food(food => {
  food
  .hunger(7)
  .saturation(7)
  // This references the function below instead of having code directly, so it is reloadable!
  .eaten(ctx => global.myAwesomeReloadableFunction(ctx))
})
})

global.myAwesomeReloadableFunction = ctx => {
  ctx.player.tell('Hello there!')
  ctx.player.tell(Text.of('Change me then reload with ').append(Text.red('/kubejs reload
startup_scripts')).append(' to see your changes!'))
}

```

Revision #10

Created 28 November 2022 07:54:22 by ChiefArug

Updated 15 November 2023 06:51:58 by Lexxie